

PRCI HOT-TAP TOOLBOX

Thermal Analysis Model for Hot-Tap Welding

PRCI THERMAL ANALYSIS MODEL FOR HOT-TAP WELDING

There are two primary concerns with welding onto in-service pipelines. The first is for welder safety during welding, since there is a risk of the welding arc causing the pipe wall to be penetrated allowing the contents to escape. The second concern is for the integrity of the pipeline following welding, since welds made in-service cool at an accelerated rate as the result of the ability of the flowing contents to remove heat from the pipe wall. These welds, therefore, are likely to have hard heat-affected zones (HAZ) and a subsequent susceptibility to hydrogen cracking. The model allows burn through risk to be controlled by limiting inside surface temperature and hydrogen cracking risk to be controlled by limiting weld-cooling rates.

Background

The Edison Welding Institute (EWI) developed the PRCI Thermal Analysis Model for Hot-Tap Welding V4.2.5 for PRCI. The model is intended to provide welding engineers with guidance for establishing safe parameters for welding onto in-service pipelines (hot-tap welding).

Software Validation

The PRCI Thermal Analysis Model for Hot-Tap Welding was validated by comparing model predictions to experimental data generated during a previous PRCI-sponsored program at EWI and to predictions made using the existing models. The Cooling Rate Prediction capability results indicate that previous model predictions tend to be non-conservative for thin wall materials, particularly at low flow rates, and very conservative for thick wall materials. The PRCI model predictions tend to be relatively accurate, with a consistent level of conservatism across wall thickness range.

Safe Practices

The use of this software model is not a substitute for procedure qualification. The model provides guidance for establishing safe parameters but provides no means for demonstrating that these parameters are practical under field conditions. To demonstrate that the parameters are practical, a welding procedure based on these predictions should be qualified under simulated conditions. (1) A brief history of cooling rate prediction methods for welds made onto in-service pipelines is given in Appendix A of the user manual.

Software Description

The PRCI Thermal Analysis Model for Hot-Tap Welding is a stand-alone, user-friendly Windows application based on a complex finite element mathematical model. The model uses a proprietary finite-element solver developed at Edison Welding Institute (EWI). Mesh generation capabilities include sleeve, branch, and bead-on pipe geometries, the latter for buttering layers and weld deposition repairs. Heat-sink capacity values can also be predicted for comparison with field measured values. The multi document user interface (MDI) allows multiple cases to be run and heat input selection curves to be generated. The model was designed and developed to meet the requirements of API 1104, API 1107, ASME Section IX, BS4515, BS6990, and CSA Z662.





The Industry Standard for Over 20 Years

CONTACT US

Toll Free: 1-866-866-6766

Phone: 713-630-0505

3801 Kirby Drive, Suite 520, Houston, Texas 77098

Sales: sales@technicaltoolboxes.com

www.technicaltoolboxes.com

PRCI HOT-TAP TOOLBOX

System Specifications

Version: 4.2.5 (Desktop)

1. Windows 7 or higher
2. 500 MB RAM
3. 100 MB free disk space

Disclaimer: This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Other names may be trademarks of their respective owners.